



# STAR HEADLIGHT & LANTERN CO.

## 255T SERIES STROBES



M255TC



M255TCM



M255TCV



M255TS



M255TSM



M255TSV

### Specifications and Features

- Protected with a low voltage shutdown feature
- Modular circuit is completely encapsulated for increased shock and weather resistance
- Field selectable flash patterns via internal jumper for single, double, or quad flash (ships in quad flash)
- RFI protection
- Durable polycarbonate, twist on/off lens
- Lightweight polycarbonate, universal flange base: three-hole, permanent mount, 1" pipe mount, optional vacuum magnet mount, and standard magnet mount with cig. plug with on/off switch
- Dimensions: tall dome: 6 11/16"H x 6 13/32"Dia.
- Dimensions: short dome: 4 3/4"H x 6 13/32"Dia
- Voltage: permanent 12-48V DC, magnet 12V DC
- Amp draw: 1.2 amps @ 12V DC, 0.6 amps @ 24V DC, 0.3 amps @ 48V DC
- Lens Colors:
- Approvals: Class II (A, B, C, R) quad flash

### Model Numbers/Descriptions:

255TC	Tall lens
255TCM	Tall lens, magnet mount
255TCV	Tall lens, vacuum magnet mount
255TS	Short lens
255TSM	Short lens, magnet mount
255TSV	Short lens, vacuum magnet mount

SF021 Rev C 5-10-2016

**STAR**  
WARNING  
SYSTEMS®

**STAR SIGNAL**  
VEHICLE PRODUCTS®

Star Headlight & Lantern Co., Inc.

455 Rochester Street  
Avon, NY 14414  
Phone: 585-226-9500  
Fax: 888-478-2797  
starheadlight.com

**BRADFORD**  
Vehicle Solutions Inc.™



PROUDLY MADE IN THE U.S.A.  
An ISO 9001:2008 Certified Company