



<b>400-600A Digital Clamp Meters</b>		
<b>PR-202A</b>		
<b>Specification</b>		
Model		PR-202A
AC Current (A)	2A/20A/200A/400A 20A/200A/600A	$\pm(1.5\%+5)$
AC Voltage (V)	2V/20V/200V/600V	$\pm(1.2\%+5)$
DC Voltage (V)	200mV/2V/20V/200V/600V	$\pm(0.8\%+1)$
Resistance ( $\Omega$ )	200 $\Omega$ /2K $\Omega$ /20K $\Omega$ /200K $\Omega$ /2M $\Omega$ /20M $\Omega$	$\pm(0.8\%+3)$
Temperature ( $^{\circ}\text{C}$ )	-40 $^{\circ}\text{C}$ ~ 1000 $^{\circ}\text{C}$	
Temperature ( $^{\circ}\text{F}$ )	-40 $^{\circ}\text{F}$ ~ 1832 $^{\circ}\text{F}$	
<b>Features</b>		
Display Count		1999
Auto Range		
Manual Range		✓
Jaw Capacity		28mm
Diode		✓
Auto Power Off		
Continuity Buzzer		✓
Low Battery Indication		✓
Data Hold		✓
MAX Mode		✓
MIN Mode		✓
Full Icon Display		
Input Impedance for DCV	Around 10M $\Omega$	✓
<b>General Characteristic</b>		
Power	<b>PR-202A-9V Battery (6F22)</b>	
LCD Size	35.6mm X 18 mm	
Product Color	Red and Grey	
Product Net Weight	220g	
Product Size	210mm X 75.6mm X30 mm	
Standard Accessories	<b>PR-202A-Batteries, Test Lead, Carrying Bag</b>	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	40 PCs	
Standard Carton Measurement	540mm X 495mm X 335mm (0.09 CBM Per Standard Carton)	
Standard Carton Gross Weight	23Kg	