



- Light and sound can be triggered separately
- integrated mounting bracket

i **TeChNICAL SpeCIFICATIONS:**

| | | | |
|---|---|--|--|
| d imensions (L x H x W): | 70 mm x 251 mm x 77 mm | | |
| Housing: | ABS | | |
| l ens: | PC, transparent | | |
| Socket: | B15d, max. 7 Watt | | |
| c onnection: | Screw terminal max. 2.5 mm ² | | |
| c able entry: | Cable diameter max. 9 mm | | |
| d uty cycle: | 100 % | | |
| Bulb included in assembly. Bulb Overview see pages 184 and 185. | | | |

ORDER SpeCIFICATIONS:

| | | | |
|---------------------|-------------------|-------------------|-------------------|
| Voltage | 24 V DC | 42 V AC | 230 V AC |
| Current consumption | 360 mA | 250 mA | 50 mA |
| red | 580 152 55 | 580 152 66 | 580 152 68 |
| yellow | 580 352 55 | - | 580 352 68 |



Further colours and voltages on request.

TeChNICAL DIAG RAMS: see page 307

See note on page 347

! ADDITIONAL INFORMATION:

please also see led /Horn c ombination 424 with add. advantages (page 196)

- High protection rating IP 65
- Horn with a life duration of up to 5,000 hrs
- LED Permanent light with a life duration of up to 50,000 hrs



- Light and sound can be triggered separately
- integrated mounting bracket

i **TeChNICAL SpeCIFICATIONS:**

| | | | |
|---------------------------------|---|--|--|
| d imensions (L x H x W): | 70 mm x 292 mm x 77 mm | | |
| Housing: | ABS | | |
| l ens: | PC, transparent | | |
| c onnection: | Screw terminal max. 2.5 mm ² | | |
| c able entry: | Cable diameter max. 9 mm | | |
| Flash frequency: | C. 1 Hz | | |
| Flash energy: | 2 Ws | | |
| l ife duration: | 4 x 10 ⁶ flashes | | |

ORDER SpeCIFICATIONS:

| | | | |
|---------------------|-------------------|-------------------|-------------------|
| Voltage | 12 V DC | 24 V DC | 230 V AC |
| Current consumption | 300 mA | 200 mA | 30 mA |
| red | - | 581 152 55 | 581 152 68 |
| yellow | 581 352 54 | 581 352 55 | 581 352 68 |



Further colours and voltages on request.

TeChNICAL DIAG RAMS: see page 308

See note on page 347

! ADDITIONAL INFORMATION:

please also see Flash/Horn c ombination 425 with add. advantages (page 197)

- High Protection rating IP 65
- Horn with a life duration of up to 5,000 hrs
- Adjustable sound output

