# \$125 series













## Ø125mm LED Revolving Warning Lights

### **(i)** Common Specifications(S125LR/ S125MLR)

- Ø125mm standard LED revolving warning lights
- Excellent omni-directional visibility with LED light collecting system and special multifaceted reflector
- Built-in buzzer available(Volume : Max 90dB at 1m)
- Revolving speed: 120-140RPM
- · Materials: Lens AS, Housing ABS, Reflector Heat resistant ABS
- Ambient operating temperature : -20°C to +50°C



## **\$125LR** LED Revolving Warning Light

- Protection rating: IP44
- · Compliant with RoHS directive

Model number	Voltage	Current	Certificates	Weight	Color
S125LR	DC12V	0.422A	-	0.43kg	<ul><li>R-Red</li><li>A-Amber</li><li>G-Green</li><li>B-Blue</li></ul>
	DC24V	0.266A		0.43kg	
	AC110V	0.082A		0.66kg	
	AC220V	0.041A		0.66kg	



Signal &

**Q**light











(Units: mm)






















Model number	Voltage	Current	Certificates	Weight	Color
S125LR	DC12V	0.422A	-	0.43kg	<ul><li>R-Red</li><li>A-Amber</li><li>G-Green</li><li>B-Blue</li></ul>
	DC24V	0.266A		0.43kg	
	AC110V	0.082A		0.66kg	
	AC220V	0.041A		0.66kg	

### **Technical Diagram**

S125LR 28 48







LED revolving warning light has Qlight's distinctive LED light collecting system and special multifaceted reflector allowing excellent omni-directional visibility. (Patent registered)

### Wiring Instructions

- External power line standard : UL1015 AWG18(0.75sq)×2C 400mm
- DC Type: Black output line is negative(-)

### Customization

- 2 buzzer sound types: Both prolonged(beep, beep) and staccato(beep, beep, beep) buzzer output available
- Same design with S125R (Model number: S125RLR)
- · Wall mount bracket options : Bracket structure allows for threading through the bracket hole or into the wall mount







Wall Mount Bracket SWP125



Wall Mount Bracket SWM125



